

Industrial pallet - TC3 - 1200 x 1000 mm - grey (with rims)



Product specifications

Uitwendig (LxBxH)	1200 × 1000 × 160 mm
Dynamic load capacity	1500 kg kg
Material	HDPE
Article number	87035841
Weight (kg)	21,5 kg
Temperature range	-30°C to +40°C, briefly up to +90°C
Color	Grey
Color European Article Number	Grey 7424902896807
European Article Number	7424902896807
European Article Number Static load capacity	7424902896807 7500 kg kg

Features

request

TC pallets runners are chamfered on both edges
Connections of the pallet chocks to the runners and the pallet surface are extra reinforced. Breakage at these sensitive points is thus reduced to a minimum
Intelligent design of the pallet chock ensures better grip of wrapping and stretch film
Raised rims around the TC3 prevent the load sliding off and mutual sliding of empty pallets
The TC pallet's patented weld geometry guarantees a high load capacity and long lifetime
Top and bottom pallet surface are completely smooth and unperforated without external rib structures
Very high load capacity that is upgradable to 1750 kg in pallet racks using reinforcing sections: on

Description

Fully enclosed plastic pallet measuring 1200 x 1000 x H160 mm. Equipped with 3 pallet runners lengthwise and raised edges all around (7 mm) on the pallet deck. The raised edges prevent goods from sliding off and empty pallets from sliding against each other. The TC3 is made of food-grade plastic. The pallet is completely smooth and hygienic, making it extremely suitable for food handling. Both the bottom of the blocks and the pallet runners are smooth and closed, without rib structures. The top and bottom of the pallet deck are also completely smooth and closed, without external rib structures, preventing dirt from entering. The runners are equipped with reinforcement ribs. The connections of the pallet blocks to the pallet runners and to the pallet deck are extra reinforced, minimizing breakage at these sensitive points. The pallet is easy to clean.



Transoplast +31(0)314 66 44 00 webshop@transoplast.com dev.transoplastshop.com