## Plastic pallet - 800 x 600 mm (3 runners - nestable)





## **Product specifications**

| Uitwendig (LxBxH)     | 800 × 600 × 145 mm |
|-----------------------|--------------------|
| Dynamic load capacity | 350 kg kg          |
| Material              | Recycled HDPE      |
| Article number        | 55.QP6080L3RR      |
| Weight (kg)           | 2,7 kg             |
| Temperature range     | -20°C to +60°C     |
| Color                 | Black              |
| Static load capacity  | 500 kg kg          |
| Edge height           | 5 mm mm            |
|                       |                    |

| Features |
|----------|
|----------|

| Nestable plastic pallet 800 x 600 mm  |  |
|---|--|
| Equipped with three runners   |  |
| Lightweight version in regenerated material   |  |
| Suitable for goods export, display applications, and storage of packaged food or car tires  |  |
| Can be stacked together to save space when empty  |  |
| Lightweight, impact-resistant, and stable   |  |
| More hygienic than wooden pallets, as plastic does not absorb moisture, pests, and bacteria |  |
| No pallet certificate required for IPPC countries   |  |

## Description

Nestable plastic pallet 800 x 600 mm. Equipped with three runners. The lightweight version in regenerated material is suitable for goods export, for display applications, but also for the storage of packaged food or for example car tires. In empty condition, the pallets can be stacked together to save space. The pallet is lightweight, impact-resistant, and stable. Exporting on a plastic pallet is more hygienic than on a wooden pallet, because plastic pallets do not absorb moisture, pests, and bacteria. A pallet certificate to IPPC countries is also unnecessary.



Transoplast +31(0)314 66 44 00 webshop@transoplast.com dev.transoplastshop.com