
Article number: 4.429.400.502 Bedrukking mogelijk

Plastic palletbox MaxiLog - 1200 x 1000 mm - on 4 feet - Grey - Perforated







Product specifications

Uitwendig (LxBxH)	1200 × 1000 × 760 mm
Inwendig (LxBxH)	1108 × 908 × 574 mm
Capacity	610 liter
Color	Grey
Sidewalls	Perforated
Material	HDPE
Article number	4.429.400.502
Weight (kg)	30,9 kg
Temperature range	-30°C to +70°C
Bottom	Perforated
Colorcode	RAL 7040
Max. load capacity per box	450 kg
Max. static stacking load	4500 kg
Max. dynamic stacking load	500 kg
Surface	Perforated
Load capacity (kg)	450

Features

- **Versatile transport solution for food and bulk goods.**
- **Outlet valve ready; 1- and 2-inch drain valves can be added.**
- **UN-approved versions available for dangerous goods.**
- **Stackable design with corner stacking features for safe storage.**
- **Smooth, easy-to-clean surfaces.**
- **Compatible with automated handling systems.**
- **Robust and sturdy, designed for industrial processing.**
- **Fully recyclable at the end of its long service life.**
- **SmartLink technology option for tracking and tracing.**
- **Available in solid or ventilated versions, with 4 feet, 2 or 3 runners.**

TRANSOPLAST
Improves your Logistics

Transoplast
+31(0)314 66 44 00
webshop@transoplast.com
dev.transoplastshop.com

Description

The MaxiLog 1200x1000x760 - on 4 feet, Ventilated pallet box is an ideal solution for transporting food or large-volume bulk goods. The reinforced base design minimizes base deformation, ensuring product integrity.
The pallet box can be stacked up to 10 units high, providing efficient storage and transport. Smooth surfaces make the box easy to clean and hygienic for use. It is available in both solid and ventilated versions, with 4 feet, 2 or 3 runners. UN-approved versions are also available for transporting dangerous goods by road, sea, and air.



Transoplast
+31(0)314 66 44 00
webshop@transoplast.com
dev.transoplastshop.com