Article number: 30.628.DB.1 Bedrukking mogelijk

# Stacking bin with lid - 600 x 400 x H 295 mm - grey

## Product specifications

| | |
|---|---|
| Uitwendig (LxBxH) | 600 × 400 × 295 mm |
| Inwendig (LxBxH) | 566 × 366 × 272 mm |
| Max. stacking load (kg) | 250 kg |
| Capacity | 55 liter |
| Handles | Closed |
| Sidewalls | Closed |
| Material | PP |
| Article number | 30.628.DB.1 |
| Weight (kg) | 2,8 kg |
| Temperature range | -20°C to +80°C |
| Color | Grey |
| Bottom | Closed, extra reinforced |
| European Article Number | 7424904137106 |
| Colorcode | RAL 7040 |
| Load capacity (kg) | 25 |

## Features

- **Featuring a reinforced diamond-pattern bottom.**
- **The standard version comes with closed handles.**
- **Lidded containers are stackable even with the lid.**
- **Lidded containers have a removable hinged lid.**
- **The lidded container is supplied with two snap-lock closures on the lid.**

TRANSOPLAST
Improves your Logistics

**Transoplast**
+31(0)314 66 44 00
webshop@transoplast.com
dev.transoplastshop.com

## Description

Plastic lidded container in Euro norm size 600 x 400 mm. The container consists of a stacking box, hinged lid, and two snap-lock closures. The lidded container is completely closed. The handles are also sealed. The bottom features a reinforced ribbed construction, making this lidded container highly suitable for heavy-duty applications. Due to its Euro norm size, it perfectly integrates with all other Euro containers, as well as with standardized pallets, mobile bases, and roll cages. Additionally, the container is stackable even with the lid. The snap-lock closures ensure secure sealing and easy reopening of the lidded container. The lockable lid prevents the cargo from getting lost, damaged, or contaminated during transportation.

## Geschikte accessoires

30.SCHARNIER

52.TR6040.4.H

52.TR6040.4.K

## Alternatieve artikelen

30.628.DB.2

30.628.DB.3

30.628.DB.4

30.628.DB.8

30.628.DB.10

30.628.DB.10.1

30.628.DB.10.2

30.628.DB.10.3

30.628.DB.10.4

30.628.DB.10.8

30.628.DB.10.6

**Transoplast**
+31(0)314 66 44 00
webshop@transoplast.com
dev.transoplastshop.com